

Technical Specifications

Inputs	6 inputs, 2 of which are optionally XLR or Cinch (CD and AUX1)
Outputs	1 x XLR 1 x Cinch 1 x Tape-out (Cinch)
Frequency Response	XLR-out, load = 600 Ω : 2.5 Hz - 600 kHz, +0/-3 dB XLR-out, load = 10 k Ω : 0.7 Hz - 600 kHz, +0/-3 dB Cinch-out, load = 10 k Ω : 0.7 Hz - 300 kHz, +0/-3 dB
Distortions	typ. < 0.0002%, 5 V rms, 10 k Ω load
Gain	XLR -> Cinch: 16 dB XLR -> XLR: 16 dB Cinch -> Cinch: 16 dB Cinch -> XLR: 16 dB
Output Impedance	XLR: < 1 Ω Cinch: < 60 Ω
Signal-to-Noise-Ratio	XLR-out: > 98 dB, based on 1 V output level (A – DIN certified) Cinch-out: > 96 dB, based on 1 V output level (A – DIN certified)
Zoom function -14dB	Control function: almost double logarithmic. Level lowering when adjusting the volume control with total amplification = x1: -14 dB; level lowering when volume control at maximum: 0 dB
Power Consumption	100 W No standby function
Remote Control	Volume, Input, Mute, Dimmer
Dimensions	450 x 150 x 360 mm (W x H x D)
Weight	12.0 kg
Finish	chrome / black ash, red ash or maple (solid wood)
Scope of Delivery	remote control with batteries, power cord, operating instructions