



THORENS MM-008 ADC

Phono Preamp for MM / MC Cartridge and integrated analog-to-digital converter with USB output

Specifications	
Kompatibilität	MM / MC Cartridge (switchable)
RIAA-accuracy	+/- 0,3 dB (20 Hz - 20 kHz)
Gain	40 dB (MM), 60 dB (MC)
Input Impedance MM	47 k Ohm + 220 pF fix
Input Impedance MC	47 k Ohm + 1 nF (load plugs to switch values)
Sensivity MM	3,29 mV RMS at -10 dBV output (316 mV RMS)
Sensivity MC	0,325 mV RMS at -10 dBV output (316 mV RMS)
Max. Output voltage	482 mV RMS at 5 mV RMS input (1 kHz)
Output impedance	47 Ohm
THD+N	<0,013% (MM) / <0,055% (MC)
Frequency response flat	20 Hz - 20 kHz +/- 0,3 dB
Frequency response -3 dB	10 Hz - 50 kHz
Signal to noise	>86 dB (MM) / >72 dB (MC)
Crosstalk	>= 40 dB
Input	RCA MM, RCA MC, RCA load plugs
Output	RCA, USB
USB Output	USB 2.0, backwards compatible USB 1.1
A/D Converter	Tenor TE7022L 24 Bit Delta Sigma
Sampling rates	8, 16, 32, 44,1, 48, 96 kHz
Operating System	Windows 10, Windows 8, Windows 7, Vista, XP, Mac OS
Power supply	external 24V DC
EAN Code	4260270220867
Power consumption	3,5 W / 15 mA
Dimensions	150 x 50 x 117 mm (W x H x D)
Finish	silver