

## Technical Specifications

<b>Operation</b>	manually
<b>Drive System</b>	exterior square drive belt
<b>Motor</b>	electronically controlled AC synchronous motor
<b>Speeds</b>	33-1/3, 45 rpm
<b>Speed Select</b>	electronically
<b>Platter</b>	12" / 4.5 kg (aluminium)
<b>Tonearm</b>	THORENS TP 300 SME 309 (optional) SME M2-9 (optional) <i>other tonearms upon request</i>
<b>Pick-up Cartridge</b>	–
<b>Anti-skating (Bias)</b>	magnetic (TP 300)
<b>Automatic Shut-off</b>	–
<b>Cable Capacitance</b>	20 pF
<b>Power Supply</b>	external controlling unit and mains adaptor (115-230 V / 50-60 Hz depending on type)
<b>Dimensions</b>	420 x 165 x 340 mm (W x H x D)
<b>Weight</b>	21.0 kg
<b>Finish</b>	silver/black or black/silver veneer (sandwich construction)
<b>Scope of Delivery</b>	mains adapter w. power cord, tonearm scale, RCA interconnects, operating instructions

## Technical Specifications

<b>Operation</b>	manually
<b>Drive System</b>	exterior square drive belt
<b>Motor</b>	electronically controlled AC synchronous motor
<b>Speeds</b>	33-1/3, 45 rpm
<b>Speed Select</b>	electronically
<b>Platter</b>	12" / 4.5 kg (aluminium)
<b>Tonearm</b>	THORENS TP 250 SME 309 (optional) SME M2-9 (optional) <i>other tonearms upon request</i>
<b>Pick-up Cartridge</b>	–
<b>Anti-skating (Bias)</b>	magnetic (TP 250)
<b>Automatic Shut-off</b>	–
<b>Cable Capacitance</b>	20 pF
<b>Power Supply</b>	external controlling unit and mains adaptor (115-230 V / 50-60 Hz depending on type)
<b>Dimensions</b>	420 x 135 x 340 mm (W x H x D)
<b>Weight</b>	12.0 kg
<b>Finish</b>	silver or black veneer
<b>Scope of Delivery</b>	mains adapter w. power cord, tonearm scale, RCA interconnects, operating instructions

## Technical Specifications

<b>Operation</b>	manually
<b>Drive System</b>	exterior square drive belt
<b>Motor</b>	electronically controlled AC synchronous motor
<b>Speeds</b>	33-1/3, 45 rpm
<b>Speed Select</b>	electronically
<b>Platter</b>	12" / 3.2 kg (aluminium)
<b>Tonearm</b>	THORENS TP 250 SME 309 (optional) SME M2-9 (optional) <i>other tonearms upon request</i>
<b>Pick-up Cartridge</b>	–
<b>Anti-skating (Bias)</b>	magnetic (TP 250)
<b>Automatic Shut-off</b>	–
<b>Cable Capacitance</b>	20 pF
<b>Power Supply</b>	external controlling unit and mains adaptor (115-230 V / 50-60 Hz depending on type)
<b>Dimensions</b>	420 x 125 x 340 mm (W x H x D)
<b>Weight</b>	8.5 kg
<b>Finish</b>	silver or black veneer
<b>Scope of Delivery</b>	mains adapter w. power cord, tonearm scale, RCA interconnects, operating instructions