

## Technical specifications

Modell	TD 903	TD 905	TD 907
Drive system: (flat precision belt)	Belt drive	Belt drive	Belt drive
Motor:	Servo-controlled AC synchronous motor	Servo-controlled AC synchronous motor	Servo-controlled AC synchronous motor
Speeds:	33 <sup>1/3</sup> , 45 U/min	33 <sup>1/3</sup> , 45 U/min	33 <sup>1/3</sup> , 45 U/min
Speed control:	Electronic	Electronic	Electronic
Platter:	ø 300 mm, weight 2.7 kg, (Quarzglass)	ø 300 mm, weight 2.7 kg, non-magnetic	ø 300 mm, weight 6.5 kg, non-magnetic
Tonearm:	Thorens TP 92/9"	Thorens TP 92/9"	Thorens TP 92/10" Optional without tonearm
Anti-skating:	Magnetic	Magnetic	Magnetic
Automatic:	No	No	No
Automatic stop:	No	No	No
Cable capacitance:	140 pF	140 pF	140 pF
Power supply:	230/115 V, 50/60 Hz	230/115 V, 50/60 Hz	230/115 V, 50/60 Hz
All-electronic motor control			
Dimensions (W x D x H):	470 x 380 x 140 mm	470 x 380 x 140 mm	470 x 380 x 140 mm
Weight:	10 kg	11 kg	12 kg